

# Punto Filo

Wall or ceiling mounted fans for intermittent ventilation of toilets (8 l/s), bathrooms (15 l/s), utility rooms (40 l/s) or kitchens (60 l/s).



- Axial fan with ultra slim front grille
- Butterfly backdraught shutter
- IPX4 Rated

## Technical Details



Code	Model	Watts	Amps	l/s	Pa	m <sup>3</sup> /hr
11123	Filo MF 100/4"	15	0.09	24	29	86.4
11127	Filo MF 100/4" <b>T</b>	15	0.09	24	29	86.4
11139	Filo MF 100/4" <b>T HCS</b>	15	0.09	24	29	86.4
11185	Filo MF 100/4" <b>PIR</b>	15	0.09	24	29	86.4
11125	Filo MF 150/6"	28	0.15	93	59	334.8
11129	Filo MF 150/6" <b>T</b>	28	0.15	93	59	334.8
11176	Filo MF 150/6" <b>T HCS</b>	28	0.15	93	59	334.8

## Product Accessories

Code	Model	For Model
22162	Filo Gasket 100/4	11123-11127-11139-11185
22164	Filo Gasket 150/6	11125-11129-11176

## Dimensions (mm)

	A	B	C	D	KG
100 / 4"	159	17	77	98	0.51
150 / 6"	214	17	96	156	0.97



## Product Code Terminology

P	Pullcord
T	Timer
A	Auto Shutter
LL	LongLife
PIR	Passive Infrared
HCS	Humidity Control System
I	Inbuilt (Recessed)
R	Reversible
M	Metal
E	ERP Compliant
Q	Quiet
D	Dual Speed
TP	Timer Programmable
ES	Energy Saving
V0	Self-Extinguishing Plastic
12V	12V Low Voltage Fan